



## 13watt 4pin Colour 827 Very Warm White



Biax™ T/E LongLast™ 4-pin  
with Amalgam, External  
Starter Req.

### Product information

Ultra compact energy saving CFL lamps with triple-tube design give an ideal light source for small fixtures and downlighters. Biax™ T lamps allow more compact fixture designs with the same lumen output as Biax™ D lamps. They can also be used to deliver higher lumen output from existing designs. The Biax™ T & T/E lamps are electrically interchangeable with Biax™ D and D/E lamps. They are available in 13, 18, 26, 32 and 42W. Light output ranges between 900 and 3200 lumens. Biax™ T/E lamps with a 4-pin electrical connection and without an internal starter are designed for high-frequency electronic ballasts. The use of separate electronic ballasts makes them suitable for almost every kind of energy supply: high and low voltages, accumulators, batteries, solar cells and systems that can be dimmed. Triple biaxial tubes





## General Characteristics

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| Wattage [W]                       | 13                                |
| Voltage [V]                       | 91                                |
| Lumens [lm]                       | 900                               |
| Cap/Base                          | GX24q-1                           |
| Bulb Shape                        | HEXPI - Hex (Triple Biax) plug-in |
| Bulb Diameter (MAX) [mm]          | 49.30                             |
| Colour temperature [K]            | 2700                              |
| Colour Rendering Index (CRI) [Ra] | 82                                |
| Colour Code                       | 827                               |
| Rated Life [h]                    | 12000                             |
| Dimming Capability                | Yes                               |
| Maximum Overall Length [mm]       | 106.20                            |
| Operating Temperature (MIN) [°C]  | -15                               |
| Minimum starting temperature [°C] | -15                               |
| Burn Position                     | U - Universal                     |
| DUN Code                          | 10043168343913                    |
| EAN Code                          | 0043168343916                     |
| Net weight per piece [g]          | 85                                |
| Gross weight per piece [g]        | 125                               |
| Pack Quantity                     | 10                                |
| Layer quantity EUR (PC)           | 320                               |
| Layer quantity UK (PC)            | 360                               |
| Pallet quantity EUR (PC)          | 2240                              |
| Pallet quantity UK (PC)           | 2520                              |
| Outer case size                   | 266 x 108 x 127 (mm)              |
| Energy Efficiency Class           | A                                 |
| Mercury Content [mg]              | 1.30                              |
| UV radiance                       | exempt                            |
| Brand                             | General Electric (GE)             |
| Product status                    | Available                         |



## Dimensions

|                             |                                   |
|-----------------------------|-----------------------------------|
| Cap/Base                    | GX24q-1                           |
| Bulb Shape                  | HEXPI - Hex (Triple Biax) plug-in |
| Bulb Diameter (MAX) [mm]    | 49.30                             |
| Maximum Overall Length [mm] | 106.20                            |
| Net weight per piece [g]    | 85                                |
| Gross weight per piece [g]  | 125                               |

## Survival Data

